

# SKANDIC

## 2010 SKANDIC® TUNDRA™ SPORT



### PACKAGE HIGHLIGHTS

- NEW REV-XU™ platform
- Pilot™ 6.9 skis
- High windshield
- Cargo rack
- Lynx Telescopic front suspension
- SC™-5M rear suspension
- Electric start
- RER™ electronic reverse
- Mountain strap
- Riser block 205 mm / 8 in

### ENGINE CHOICE    COLOR CHOICE

Rotax® 550F                      Yellow / Black

### ENGINE

Engine	Rotax 550F
Engine details	Axial fan-cooled, cylinder reed porting
Cylinders	2
Displacement	553.4 cc / 33.8 in <sup>3</sup>
Bore	76 mm / 3 in
Stroke	61 mm / 2.4 in
Max. engine speed	6900 RPM
Carburetion	2X VM-30
Recommended fuel type	Regular unleaded
Min. octane	87
Fuel tank	40 liters / 10.6 gallons
Oil tank capacity	3.7 liters / 3.9 quarts
Exhaust system	Single tuned-pipe, baffle muffler

### POWERTRAIN

Drive clutch type	TRA™ III
Driven clutch type	LPV VSA
Engagement	2500 RPM
Small sprocket number of teeth	17
Large sprocket number of teeth	45
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm / 7.2 in
Brake system	Hydraulic

### SUSPENSION

Front suspension	LTS
Front shock	Motion Control
Front suspension max. travel	150 mm / 6 in
Rear suspension	SC-5M
Center shock	Motion Control
Rear shock	HPG
Rear suspension max. travel	381 mm / 15 in

### DIMENSIONS

Vehicle overall length	3069 mm / 120.8 in
Vehicle overall width	1002 mm / 39.4 in
Vehicle overall height	1278 mm / 50.3 in
Official dry weight	207 kg / 456 lb
Ski stance	813 mm / 32 in
Ski overall length	1066 mm / 42 in
Ski width	175 mm / 6.9 in
Track nominal width	406 mm / 16 in
Track nominal length	3486 mm / 137 in
Track profile height	31.8 mm / 1.25 in

### FEATURES

Frame	REV-XU	Handlebar	Painted steel / Riser block	Heated throttle lever	Standard	Mirrors	Optional
Skis	Pilot 6.9		(205 mm / 8 in) / Mountain strap	Heated grips	Standard	Windshield	395 mm / 15.5 in
Seating	1-up	Electric start	Standard	Speedometer	Standard	Carbide runner	Standard
		Reverse	RER	Tachometer	Standard	Hitch	Optional
				Fuel gauge	Standard		