

SKANDIC

2010 SKANDIC® SWT



PACKAGE HIGHLIGHTS

- Rotax® V-800 4-TEC® four-stroke engine
- Yeti II platform
- 24 x 156 x 1.25-inch track
- Synchromesh transmission w/ reverse
- Electric start
- High windshield
- Windshield mirrors
- Two-up seat with backrest, underseat storage
- Cargo rack
- Hitch
- Mountain strap
- 12V power outlet

ENGINE CHOICE COLOR CHOICE

Rotax V-800	Yellow / Black
-------------	----------------

ENGINE

Engine	Rotax V-800
Engine details	Liquid-cooled, four-stroke
Cylinders	2
Displacement	799.9 cc / 48.8 in ³
Bore	91 mm / 3.6 in
Stroke	61.5 mm / 2.4 in
Max. engine speed	7250 RPM
Carburetion	EFI
Recommended fuel type	Regular unleaded
Min. octane	87
Fuel tank	42 liters / 11.1 gal
Engine oil capacity	2.2 liters / 2.3 quarts
Exhaust system	Exhaust pipe, muffler

POWERTRAIN

Drive clutch type	TRA™ IV
Driven clutch type	NDT 6K VSA
Engagement	2500 RPM
Drive sprocket number of teeth	8
Drive sprocket diameter	158.7 mm / 6.2 in
Brake system	Hydraulic

SUSPENSION

Front suspension	LTS
Front shock	Hydraulic
Front suspension max. travel	150 mm / 6 in
Rear suspension	Easy ride XWLS
Center shock	Hydraulic
Rear shock	Hydraulic
Rear suspension max. travel	215 mm / 8.5 in

DIMENSIONS

Vehicle overall length	3070 mm / 120.9 in
Vehicle overall width	1155 mm / 45.5 in
Vehicle overall height	1355 mm / 53.3 in
Official dry weight	326 kg / 717 lb
Ski stance	900 mm / 35.4 in
Ski overall length	1112 mm / 43.8 in
Ski width	250 mm / 9.8 in
Track nominal width	600 mm / 24 in
Track nominal length	3968 mm / 156 in
Track profile height	31.8 mm / 1.25 in

FEATURES

Frame	Yeti II	Electric start	Standard	Tachometer	Optional	Windshield	High
Skis	ADJ w/ liner	Reverse	Mechanical	Fuel gauge	Optional	Carbide runner	Standard
Seating	2-up modular w/box	Heated throttle lever	Standard	Temperature gauge	Optional	Hitch	Tongue type
Backrest	Standard	Heated grips	Standard	Mirrors	Standard		
Handlebar	Straight w/strap	Speedometer	Standard				

